

EasyView™ Lite Series

Indoor Dome Camera

CD-H2N

NTSC



CD-H2N



KEY FEATURES

- 1/3" CCD Sensor
- 600 TV Lines
- 2.9mm Fixed Lens
- 0.2 Lux (Color)
- AWB: Automatic Tracking White Balance
- 12VDC

CONSTRUCTION

- 3" Polycarbonate Bubble
- 3-Axis Gimbal
- Ivory or Black Plastic Housing
- Compact Size

AVAILABLE MODELS

- CD-H2N-I (Ivory Housing) - 2.9mm
- CD-H2N-B (Black Housing) - 2.9mm

AVAILABLE ACCESSORIES



CD-WMI200 (Ivory)
Indoor Wall Mount



CD-WMB200 (Black)
Indoor Wall Mount


TECHNICAL SPECIFICATIONS

Technical Specifications	CD-H2N
Video Format	NTSC
Image Sensor	1/3" CCD
Horizontal Resolution	600 TV Lines
Day/Night Functionality	No
Lens Type	Fixed 2.9mm
Angle of View	120°
IR LED	N/A
IR LED Distance	N/A
LED Illumination Angle	N/A
Sync System	Internal
Effective Pixels	768(H) x 494(V)
Scanning System	525 Lines, 2:1 Interlaced
Electronic Shutter	1/60 ~ 1/100,000 sec.
Main Video Output	1.0 Vp-p Composite, 75 ohm
Service Monitor Output	No
Minimum Illumination	0.2 Lux (Color)
S/N Ratio	More than 48dB (AGC Off)
General Information	CD-H2N
Operating Temperature	23°F ~ 113°F (-5°C ~ +45°C)
Operating Humidity	Within 90% RH
Power Consumption	500mA
Input Voltage	12VDC

*Specifications are subject to change without any prior notice.

3-AXIS GIMBAL, SIMPLY MOUNT AND POINT

EasyView™ Lite series cameras all have 3-axis Gimbals with pan, tilt, and rotating ability for easy installation and placement. Simply mount the camera to any sturdy surface, then adjust the Gimbal until the camera points to the area you want monitored.



DIMENSIONS

Unit: Inches (mm)

